


Mini Series

Constant Current LED Driver

LED恒流驱动器



Model No. 型号	Input voltage 额定电压 (V)	Max. output power 功率 (W)	Output current 输出电流 (mA)	Output voltage 输出电压 (V)	Power factor 功率因数 (λ)	Efficiency full load 效率 (%)	No-load power 空载功率 (W)	Ambient temperature 环境温度 ta (°C)	Max. casing temperature 最大外壳温度 tc (°C)	Isolation 隔离	Dimensions LxWxH 尺寸 (mm)	Weight 重量 (g)
MINI350mA/6W	100-240	6	350	3-17	0.4C	80	<0.3	-20...+50	80	SELV	50x32x18.5	30
MINI500mA/6W	100-240	6	500	3-12	0.4C	79	<0.3	-20...+50	80	SELV	50x32x18.5	30
MINI700mA/6W	100-240	6	700	3-8	0.4C	73	<0.3	-20...+50	80	SELV	50x32x18.5	30

- Super compact design
- Driver for built-in use
- Universal AC input
- Input and output terminal blocks on the same side
- Open circuit, short circuit, over load and overheating protection
- Simple installation
- SELV class II output
- IP20 design
- 超小体积紧凑设计
- 内置式驱动运用
- 全电压输入规格AC100-240V
- 同侧输入和输出端接线端子规格
- 输出开路, 短路, 过载和超温保护
- 安装经济便捷
- SELV和II类等级
- 防护等级IP20

